



Installation Manual:

F80x M4/M3 Equal Length (EL) Mid-Pipe-AWE

DISCLAIMER

The below information assumes that the purchaser has signed the “Off Road Use Only Waiver” form that can be found at the following url:

<http://images.activeautowerke.com/Installation%20PDF%27s/vehiclewaiver2.pdf>

The above waiver must be signed and submitted to Active Autowerke prior to purchase of the performance products.

Prior to beginning the installation process – please read the following instruction manual carefully and in full. Ensure that all necessary parts are available to perform the complete installation.

By the Installation of the Active Autowerke Equal Length (EL) Mid-Pipe (AA-EXHF7XMEL-MIDPIPE++KIT) – you are agreeing to all terms and conditions stated below:

- The purchaser assumes full responsibility for the use of these products on their automobiles which may or may not conform to applicable laws and regulations for on road or highway use.
- The purchaser acknowledges that Active Autowerke states that products are intended for off road or racetrack use only
- The purchaser agrees that Active Autowerke shall bear no responsibility in ensuring that their automobiles are compliant with State, Federal, Provincial, or local ordinances and emissions authorities.
- The waiver of compliance shall cover all past and future purchases from Active Autowerke.
- Active Autowerke assumes no responsibility for damages occurring from misuse, abuse, improper installation, improper operation, lack of responsible care, or part incompatibility issues.

WARRANTY INFORMATION

Included with your purchase of Active Autowerke premium performance products is a warranty card. This warranty card states the following:

Active Autowerke provides a limited one-year warranty against material defects and workmanship for one year (starting from the date of the original purchase). Warranty only applies to the original purchaser and is non-transferrable.

Exceptions to the warranty include but are not limited to “wear and tear” such as brake rotors, brake pads, flywheels and clutches and “garage sale” items (of which deposits and sales are FINAL and non-refundable).

Warranty will be VOID if:

- The product is abused, misused, or improperly maintained.
- Repairs have been made or attempted by anyone other than an authorized Active Autowerke repair or maintenance facility.
- Repairs are required due to normal “wear and tear” and regular usage.
- Alterations or Modifications are made to the original Active Autowerke Product®
- The Product is classified as “Consumable.”
- The Product has been involved in an automobile accident or there is excessive damage to the product not caused by material workmanship or material defects.

The warranty is limited to repairs and/or replacements of the product or part(s) found to be defective without additional charges to the purchaser. Active Autowerke reserves the right to refund the complete purchase price for the defective item ONLY and will not be held liable for losses or damages arising from the defect.


If a part component from Active Autowerke product, system, kit is found to be defective – this warranty shall only apply to the defective part or component and shall not require Active Autowerke to repair, replace, or refund the complete Active Autowerke product, system or kit.

MINIMUM REQUIRED TOOLS

- Lubrication Spray
- Sawzall or Preferred Cutting Tool
- Deep Socket 11mm
- Deep Socket 13mm
- Deep Socket 15mm
- Torx T50
- Large Flathead Screwdriver
- Spacer Block (Included in the Kit)
- E10 Torx




F80x M4/M3 Equal Length Kit (Included Parts):



Pictured: Equal Length Mid-Pipe, AWE Pipes, Clamps, and Active Autowerke Center Plate.


- Active Autowerke Mid-Pipe
- Active Autowerke AWE (Pipe A – Passenger Side)
- Active Autowerke AWE (Pipe B – Driver's Side)
- Ball Clamps 65mm (2)
- Torca Slip Clamps 65mm (2) – To be re-used from existing AWE system (Not included in the Kit)
- Active Autowerke F Brace (Center Plate)

*Note: This version displays the kit with AWE Pipes. There are 3 different Kit versions – please ensure that the correct version is ordered to meet your correct specifications.



Step 1 Separate AWE mid pipe from AWE rear:

Customers using an Active Autowerke Mid-Pipe with a AWE M3/M4 rear exhaust will be required to separate the AWE Mid-Pipe from the rear pan.



Step 2 Separating the AWE Mid-Pipe from Rear Exhaust
Picture for illustration purposes.


Loosen the clamps in the area shown above (in front of the differential)

Step 3 Remove Mid pipe from Down pipes:



Step 4 Remove Nuts


Remove 11mm nuts – The Torx Bolts for the alignment plate can remain in place.



Step 5 Remove Center Plate

Remove 6mm Allen Bolts from the Center Brace.

Replace with Active Autowerke F-Brace (included in Kit – Shown Below)





Step 6 Remove Transmission Mount

Support the exhaust system with a suitable jack for safety.

Remove the Gray Transmission Mount (E10 Torx)



Step 7: Remove AWE Mid-Pipe (Picture for illustration)

Carefully remove entire mid-pipe from the vehicle, ensuring that all bolts and parts are kept safely for installation of the new mid-pipe.



Step 8 Re-Install Mounts

Place the three exhaust mounts removed from the original mid-pipe onto the new mid-pipe. Lubricate liberally to ensure mounts fit securely in place.



Step 9 Install Mid-Pipe


Install the new mid-pipe. Tighten drivers' side (Left side) first, this will help center the mid pipe in the tunnel. Tighten right side.



Established 1981

Step 10 Transmission Mount


Use the transmission mount to support during installation.



Step 11 Install Active Autowerke Center Plate

Space mid-pipe above brace leaving half an inch of space (0.5 inches). The installation kit includes a foam spacer that can be used to ensure there is adequate space (as seen the image above) – remove spacer after the bolts have been tightened.


****Note:** Resonated Pipes are being shown in this image. Appearance will differ slightly for Non-Resonated and AWE Kit Versions.



Step 12 Mount Connecting Pipe A


Slide part A (Right-passenger) pipe on to AWE rear exhaust pipe, repeat for part B (Drivers – Left) side. Slide on Band clamps.

*Note: Mount Part Rear A shown in the image above will be installed on the passenger side.




Step 13 Mount Connecting Pipe B


*Note: Mount Part Rear B in the image above will be installed on the driver's side.



Step 14 Tighten Ball Clamps

Slide on the ball clamps. Align cups of small pipes with balls of mid pipe. Slide Ball clamps in place. Begin with the bolt heads on the inside. The ball clamps will be positioned facing towards the outside when tightened as seen in the image below.





Step 15 Recheck and Review Work

Re-Check all clamps and re-tighten all nuts and bolts associated with the installation. Ensure everything is properly secured and tightened.